

# AUTOHAZE EXTRA

## High Caustic Ghost Image Remover

### DESCRIPTION

Autohaze Extra is a light coloured aqueous mixture of potassium hydroxide and solvent.

#### Applications

Autohaze Extra has been formulated for effective removal of hazes and ghost images commonly left after stencil reclaiming. It negates the need for an additional solvent application.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

### FEATURES & BENEFITS

- A convenient 'one pot' haze remover liquid based on a unique caustic and solvent mixture. Allows rapid and effective removal of ink stains and ghost images in less than 10 minutes.
- Ideal for busy print shops or where maximum haze removal performance is needed.

### WORKING INSTRUCTIONS

#### To remove Stains or Ghost Images

1. Clean off all ink residue prior to stencil removal.
2. Remove stencil with a recommended Autotype decoating chemical product.
3. Apply a small amount of Autohaze Extra to both sides of the dry mesh with a brush, thoroughly covering the stained areas in a circular motion.
4. Leave to stand for 10 minutes. If left to stand for longer periods, Autohaze Extra can damage the fibres of the mesh.
5. Rinse off residue with gently water spray.
6. Remove stain with a high pressure gun.



**To remove very difficult Stains**

1. Before rinsing off the Autohaze Extra, apply a small amount of Autosolve Industrial AF screen wash as an 'activator' and work in well to the stain.
2. Leave to stand for 1 minute before rinsing with a gentle water spray followed by the high pressure rinse.

Due to partial separation, Autohaze Extra may require mixing if left to stand for long periods. Autohaze Extra may also be used to degrease and chemically abrade new or used aluminum frames prior to mesh stretching.

For more information on how to use MacDermid Autotype products, go to the How to Guide section at [macdermid.com/autotype](http://macdermid.com/autotype).

**SHELF LIFE & STORAGE**

Autohaze Extra should be stored between 5 to 25 °C (40 to 77 °F). Do not freeze or heat.

Shelf life at these conditions is two years.

**PACKAGING**

Autohaze Extra is available in trade packs of 12 x 1 Kg and 2 x 5 Kg.



**SAFETY & WARNING**

MacDermid Autotype recommends that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use.

**Safety Data Sheets are available from MacDermid Autotype.**

**WASTE TREATMENT**

Prior to using any recommendations or suggestions by MacDermid Autotype for waste treatment, the user is required to know the appropriate local/state/federal regulations for on-site or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

**CONTACT INFORMATION**

**To confirm this is the most recent issue, please contact MacDermid Autotype**  
 salessupport@macdermidautotype.com

<b>North America</b> MacDermid Autotype Inc. 5210 Phillip Lee Drive Atlanta, GA 30336, USA (404) 696 4565 autotypeusinfo@macdermid.com	<b>Europe</b> MacDermid Autotype Ltd. Grove Road, Wantage, Oxon OX12 7BZ, UK +44 (0) 1235 771111 salessupport@macdermidautotype.com	<b>Asia</b> MacDermid Autotype Pte Ltd. No, 20 Tuas Avenue 6, Singapore, 639307 +65 689 79670 sginfo@autotype.com
---	--	--

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product.  
 READ IT THOROUGHLY PRIOR TO PRODUCT USE.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

® Registered Trademark of MacDermid Performance Solutions. ™ Trademark of MacDermid Performance Solutions.  
 © Platform Specialty Products Corporation and its subsidiaries 2016.

