

# AUTOKLEEN PLUS

## Ghost Image and Gelatine Stencil Remover

### DESCRIPTION

A highly effective, low caustic haze remover. Used by itself or in conjunction with Autosolve solvents. Less aggressive to meshes than high caustic haze removers.

### Applications

All types of ghost images on screens.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

### FEATURES & BENEFITS

- Autokleen Plus is used for removal of ghost images and diazo stains on mesh, and can also be used for decoating gelatine indirect stencils. It can be used in conjunction with "Autosolve Industrial AF" screen cleaning solvent for the effective removal of ghost images and ink stains. It is a simple to use, fast acting solution designed for manual application only. It is not recommended for use in automatic decoating machines.
- The low Sodium Hydroxide content (<5%) makes Autokleen Plus an effective alternative to more aggressive haze removal products such as Autohaze (caustic content >20%).
- Effective results without the use of harmful or high hazard haze remover systems.

### WORKING INSTRUCTIONS

#### For the removal of Diazo stains on mesh

1. After removing ink and stencil, apply Autokleen Plus onto both sides of mesh.
2. Allow to dry. Do not use heat.
3. Wash off with strong water spray, followed by a high pressure gun.

#### For the removal of Ghost Images and ink stains

1. Apply Autokleen Plus and allow to dry.
2. Apply a water miscible Autosolve screen wash (eg Autosolve Graphics or Autosolve Industrial AF) to both sides of mesh and leave for 2 minutes.
3. Wash off with strong water spray, followed by a high pressure gun.



Do not directly mix Autokleen Plus with an Autosolve screen wash, as heat may be generated with release of toxic gas.

For more information on how to use MacDermid Autotype products, go to the How to Guide section at [macdermid.com/autotype](http://macdermid.com/autotype).

#### **SHELF LIFE & STORAGE**

Autokleen Plus should be stored between 5 to 30 °C (40 to 86 °F). Do not freeze.

Shelf life at these conditions is one year.

#### **PACKAGING**

Autokleen Plus is available in trade packs of 12 x 1 Litre, 2 x 5 Litre, 1 x 25 Litre and 1 x 200 Litre.



**SAFETY & WARNING**

MacDermid Autotype recommends that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use.

**Safety Data Sheets are available from MacDermid Autotype.**

**WASTE TREATMENT**

Prior to using any recommendations or suggestions by MacDermid Autotype for waste treatment, the user is required to know the appropriate local/state/federal regulations for on-site or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

**CONTACT INFORMATION**

**To confirm this is the most recent issue, please contact MacDermid Autotype**  
 salessupport@macdermidautotype.com

<b>North America</b> MacDermid Autotype Inc. 5210 Phillip Lee Drive Atlanta, GA 30336, USA (404) 696 4565 autotypeusinfo@macdermid.com	<b>Europe</b> MacDermid Autotype Ltd. Grove Road, Wantage, Oxon OX12 7BZ, UK +44 (0) 1235 771111 salessupport@macdermidautotype.com	<b>Asia</b> MacDermid Autotype Pte Ltd. No, 20 Tuas Avenue 6, Singapore, 639307 +65 689 79670 sginfo@autotype.com
---	--	--

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product.  
 READ IT THOROUGHLY PRIOR TO PRODUCT USE.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

® Registered Trademark of MacDermid Performance Solutions. ™ Trademark of MacDermid Performance Solutions.  
 © Platform Specialty Products Corporation and its subsidiaries 2016.

