

AUTOSOLVE GRAPHICS

Ink Cleaning Solvent for Printing Inks

DESCRIPTION

The product has low flammability, low volatility and contain chemicals less harmful to operators than traditional cleaning solvents.

Applications

 The product has been formulated specifically for the removal of those inks commonly used for Graphics screen printing.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS

- Hazard-label-free solvent for cleaning screens after printing. Effective on a wide variety
 of 'graphics' inks, including paper and board, vinyl and UV curing types. Low evaporation
 rate reduces VOC emissions, solvent odours and allows longer dwell times for improved
 ink removal.
- Safer than 'traditional' screen cleaning solvents. Improved print shop environment.
 Effective on a wide range of ink types allowing only one solvent to be used. Low evaporation rate allows longer dwell times for improved ink removal. Can be used in recirculation equipment and automatic cleaning machines.

WORKING INSTRUCTIONS

To remove ink prior to stencil reclaiming

- 1. For best results apply Autosolve Graphics as soon as possible after printing, before ink has dried in. Apply to both sides of the screen with a brush.
- 2. Leave to stand for 2 minutes whilst ink residue is softened. The low volatility of this product allows longer dwell times than traditional cleaning solvents, for improved ink removal with reduced staining.
- 3. Wash both sides of the screen thoroughly with water to remove all traces of solvent. Note always rinse chemicals off the screen before using a high pressure gun. The screen is now ready to be decoated.

For more information on how to use MacDermid Autotype products, go to the How to Guide section at macdermid.com/autotype.





TECHNICAL DATA SHEET

SHELF LIFE & STORAGE

Autosolve Graphics should be stored between 0 to 30 °C (30 to 86 °F). Do not heat.

Shelf life at these conditions is two years.

PACKAGING

Autosolve Graphics is available in trade packs of 6 x 1 Litre, 2 x 5 Litre, 1 x 25 Litre and 1 x 210 Litre.





TECHNICAL DATA SHEET

SAFETY & WARNING

MacDermid Autotype recommends that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use.

Safety Data Sheets are available from MacDermid Autotype.

WASTE TREATMENT

Prior to using any recommendations or suggestions by MacDermid Autotype for waste treatment, the user is required to know the appropriate local/state/federal regulations for onsite or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

CONTACT INFORMATION

To confirm this is the most recent issue, please contact MacDermid Autotype salessupport@macdermidautotype.com

North America

MacDermid Autotype Inc. 5210 Phillip Lee Drive Atlanta, GA 30336, USA (404) 696 4565 autotypeusinfo@macdermid.com

Europe

MacDermid Autotype Ltd. Grove Road, Wantage, Oxon OX12 7BZ, UK +44 (0) 1235 771111 salessupport@macdermidautotype.com

Asia

MacDermid Autotype Pte Ltd. No, 20 Tuas Avenue 6, Singapore, 639307 +65 689 79670 sginfo@autotype.com

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product. READ IT THOROUGHLY PRIOR TO PRODUCT USE.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF ITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

® Registered Trademark of MacDermid Performance Solutions. TM Trademark of MacDermid Performance Solutions. © Platform Specialty Products Corporation and its subsidiaries 2016.

