

AUTOSTRIP COMBI

Combination Ink and Stencil Remover

DESCRIPTION

Autostrip Combi is a combined ink and stencil remover for textile/garment printing that can either be applied manually, or used in a dip tank. This one step process saves time and money as both the ink and stencil are removed in one operation.

Applications

- This product has been formulated specifically for the removal of those inks and stencils commonly used for textile screen printing.
- Autostrip Combi is suitable for dip tank and manually by spray or brush.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS

- Perfect for use in a dip tank. Works with all direct stencils.
- Saves both time and money.

WORKING INSTRUCTIONS

The product is sold as a concentrate for dilution with water. Typical dilution ratios are 1:10 for dip tank and 1:5 for manual use.

To remove ink and stencil:

Manually (with a brush).

1. For best results apply Autostrip Combi as soon as possible after printing, before ink has dried in. Apply to both sides of the screen with a brush.
2. Leave to stand for 2 minutes whilst ink residue and stencil is softened. The low volatility of this product allows longer dwell times than traditional cleaning solvents, for improved ink removal with reduced staining.
3. Wash both sides of the screen thoroughly with water to remove all traces of solvent. The screen is now ready to be high pressure gunned.



Dip Tank:

1. For best results place screen in to Autostrip Combi as soon as possible after printing, before ink has dried in.
2. Leave in dip tank for up to 20 minutes whilst ink residue and stencil is softened.
3. Wash both sides of the screen thoroughly with water to remove all traces of solvent. The screen is now ready to be high pressure gunned.

For more information on how to use MacDermid Autotype products, go to the How to Guide section at macdermid.com/autotype.

SHELF LIFE & STORAGE

Autostrip Combi should be stored between 5 to 30 °C (40 to 86 °F). Do not freeze.

Shelf life at these conditions is one year.

PACKAGING

Autostrip Combi is available in trade packs of 2 x 5 Litre, 1 x 25 Litre and 1 x 210 Litre.



SAFETY & WARNING

MacDermid Autotype recommends that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use.

Safety Data Sheets are available from MacDermid Autotype.

WASTE TREATMENT

Prior to using any recommendations or suggestions by MacDermid Autotype for waste treatment, the user is required to know the appropriate local/state/federal regulations for on-site or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

CONTACT INFORMATION

To confirm this is the most recent issue, please contact MacDermid Autotype
salesupport@macdermidautotype.com

North America MacDermid Autotype Inc. 5210 Phillip Lee Drive Atlanta, GA 30336, USA (404) 696 4565 autotypeusinfo@macdermid.com	Europe MacDermid Autotype Ltd. Grove Road, Wantage, Oxon OX12 7BZ, UK +44 (0) 1235 771111 salesupport@macdermidautotype.com	Asia MacDermid Autotype Pte Ltd. No, 20 Tuas Avenue 6, Singapore, 639307 +65 689 79670 sginfo@autotype.com
---	--	---

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product.
 READ IT THOROUGHLY PRIOR TO PRODUCT USE.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

® Registered Trademark of MacDermid Performance Solutions. ™ Trademark of MacDermid Performance Solutions.
 © Platform Specialty Products Corporation and its subsidiaries 2016.

