

AUTOSTRIP POWDER

Direct Stencil Decoating Powder

DESCRIPTION

Autostrip Powder dissolves cleanly without particles making it perfect for use with decoating machines or for manual application.

Applications

Autostrip Powder is used for removal of all direct stencils, eg PLUS Emulsions and Capillex.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

FEATURES & BENEFITS

- Easy to use and fast to dissolve. Very effective stencil decoater.
- Autostrip Powder offers easy storage and handling but must be mixed with the prescribed amount of water before use.

WORKING INSTRUCTIONS

Mixing of Autostrip Powder

For general use dissolve 100 grams in 10 litres (18 pints) of cold water to make 1% strength solution. When stencils are difficult to remove use 5 litres of cold water to make a 2% strength solution. If an Automatic Stripping machine is used a 2% solution strength is preferred for a longer solution life.

Use of Autostrip Powder

1. Remove all ink residues by applying Autosolve Screen Wash to both sides of the mesh and work in with a brush.
2. Wash both sides of mesh with water to remove all solvent traces.
3. With a brush, apply Autostrip liberally to both sides of the mesh.
4. Leave to stand for 3 to 5 minutes while the emulsion coating dissolves. Do not allow Autostrip to dry onto the screen as this will make the stencil difficult to remove.
5. Wash off the stencil with a strong spray followed by a high pressure gun.



For more information on how to use MacDermid Autotype products, go to the How to Guide section at macdermid.com/autotype.

SHELF LIFE & STORAGE

Autostrip Powder should be stored between 5 to 30 °C (40 to 86 °F). Do not heat.

Shelf life at these conditions is two years.

PACKAGING

Autostrip Powder is available in 1 x 15 Kg only. Please note that due to the hazard classification, supply restrictions apply to this product.



SAFETY & WARNING

MacDermid Autotype recommends that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use.

Safety Data Sheets are available from MacDermid Autotype.

WASTE TREATMENT

Prior to using any recommendations or suggestions by MacDermid Autotype for waste treatment, the user is required to know the appropriate local/state/federal regulations for on-site or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

CONTACT INFORMATION

To confirm this is the most recent issue, please contact MacDermid Autotype
 salessupport@macdermidautotype.com

North America MacDermid Autotype Inc. 5210 Phillip Lee Drive Atlanta, GA 30336, USA (404) 696 4565 autotypeusinfo@macdermid.com	Europe MacDermid Autotype Ltd. Grove Road, Wantage, Oxon OX12 7BZ, UK +44 (0) 1235 771111 salessupport@macdermidautotype.com	Asia MacDermid Autotype Pte Ltd. No, 20 Tuas Avenue 6, Singapore, 639307 +65 689 79670 sginfo@autotype.com
---	--	--

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product.
 READ IT THOROUGHLY PRIOR TO PRODUCT USE.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

® Registered Trademark of MacDermid Performance Solutions. ™ Trademark of MacDermid Performance Solutions.
 © Platform Specialty Products Corporation and its subsidiaries 2016.

