

## DELTA II

### Laser Imageable Film Positive

#### DESCRIPTION

Laser imageable film positive. An anti-static polyester based film with two sided toner receptive coating, which can be imaged on either side with a standard laser printer or photocopier.

#### Applications

- Laser Imageable film positive. An anti-static polyester based film with two sided toner receptive coating, which is imaged via standard laser printer or photocopier.
- Delta II is used to produce laser imageable film positives for exposure to photostencil systems in the screen printing industry.
- Delta requires no post chemical process and is ideal for screen printing applications.

READ ENTIRE TECHNICAL DATA SHEET BEFORE USING THIS PRODUCT

#### FEATURES & BENEFITS

- Anti-static two sided coating.
- Simple to use.
- Low cost.

#### WORKING INSTRUCTIONS

1. Prepare the artwork on screen.
2. Image film as if printing onto normal paper:
  - a. Handle film at edge to avoid marking.
  - b. Always run a print test to ensure optimum performance.
  - c. Print on a laser printer.

For more information on how to use MacDermid Autotype products, go to the How to Guide section at [macdermid.com/autotype](http://macdermid.com/autotype).



**SHELF LIFE & STORAGE**

Correct storage conditions are at a temperature of 5 to 20 °C (40 to 86 °F).

Shelf life at these conditions is 24 months.

**PACKAGING**

Delta II is available in A4 and A3 sizes, in packs of 100 sheets.



**SAFETY & WARNING**

MacDermid Autotype recommends that the company/operator read and review the Safety Data Sheets for the appropriate health and safety warnings before use.

**Safety Data Sheets are available from MacDermid Autotype.**

**WASTE TREATMENT**

Prior to using any recommendations or suggestions by MacDermid Autotype for waste treatment, the user is required to know the appropriate local/state/federal regulations for on-site or off-site treatment which may require permits. If there is any conflict regarding our recommendations, local/state/federal regulations take precedent.

**CONTACT INFORMATION**

**To confirm this is the most recent issue, please contact MacDermid Autotype**  
[salessupport@macdermidautotype.com](mailto:salessupport@macdermidautotype.com)

<b>North America</b> MacDermid Autotype Inc. 5210 Phillip Lee Drive Atlanta, GA 30336, USA (404) 696 4565 <a href="mailto:autotypeusinfo@macdermid.com">autotypeusinfo@macdermid.com</a>	<b>Europe</b> MacDermid Autotype Ltd. Grove Road, Wantage, Oxon OX12 7BZ, UK +44 (0) 1235 771111 <a href="mailto:salessupport@macdermidautotype.com">salessupport@macdermidautotype.com</a>	<b>Asia</b> MacDermid Autotype Pte Ltd. No, 20 Tuas Avenue 6, Singapore, 639307 +65 689 79670 <a href="mailto:sginfo@autotype.com">sginfo@autotype.com</a>
---	--	---

Also read carefully warning and safety information on the Safety Data Sheet. This data sheet contains technical information required for safe and economical operation of this product.  
 READ IT THOROUGHLY PRIOR TO PRODUCT USE.

DISCLAIMER: All statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed. No statement or recommendation shall constitute a representation unless set forth in an agreement signed by officers of seller and manufacturer. NO WARRANTY OR MERCHANTABILITY OR WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE. The following warranty is made in lieu of such warranties and all other warranties, express, implied, or statutory. Products are warranted to be free from defects in material and workmanship at the time sold. The sole obligation of seller and manufacturer under this warranty shall be to replace any product defective at the time sold. Under no circumstances shall manufacturer or seller be liable for any loss, damage or expense, direct or consequential, arising out of the inability to use the product. Notwithstanding the foregoing, if products are supplied in response to a customer request that specifies operating parameters beyond those stated above, or if products are used under conditions exceeding said parameters, the customer by acceptance or use thereof assumes all risk of product failure and of all direct, indirect and consequential damages that may result from use of the products under conditions, and agrees to exonerate, indemnify and hold harmless MacDermid Incorporated therefrom. No suggestion for product use nor anything contained herein shall be construed as a recommendation to use any product in infringement of any patent rights, and seller and manufacturer assume no responsibility or liability for any such infringement.

® Registered Trademark of MacDermid Performance Solutions. ™ Trademark of MacDermid Performance Solutions.  
 © Platform Specialty Products Corporation and its subsidiaries 2016.

